


IGBT 62mm 半桥模块

Features

- 1200V 200A
- $V_{CE(sat)(typ.)} = 2.6V @ V_{GE} = 15V, I_C = 200A$
- High speed switching
- Higher system efficiency
- Soft current turn-off waveforms



General Description

JIAEN FS IGBTs offer lower losses and higher energy efficiency
 For general inverter and other soft switching applications.

IGBT Maximum Rated Values ($T_C=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Value	Units
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Continuous Collector Current ($T_C=25^\circ C$)	300	A
	Continuous Collector Current ($T_C=80^\circ C$)	200	A
I_{CRM}	Repetitive Peak Collector Current (tp= 1 ms)	400	A
P_D	Maximum Power Dissipation ($T_C=25^\circ C$)	1040	W

IGBT Characteristics ($T_C=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$V_{GE}=15V, I_C=200A$	-	2.6	3.1	V
	Collector-Emitter Saturation Voltage	$V_{GE}=15V, I_C=200A$	-	3.1	-	V
$V_{GE(th)}$	Gate Threshold Voltage	$V_{GE}=V_{CE}, I_C=8mA$	5.0	6.0	7.0	V
Q_g	Total Gate Charge	$V_{GE}=-15V...+15V$	-	3.2	-	μC
R_g	Gate Resistance	$V_{GE}=0V, f=1MHz$	-	5	-	Ω
C_{ies}	Input Capacitance	$V_{CE}=25V$ $V_{GE}=0V$ $f=1MHz$	-	14	-	nF
C_{oes}	Output Capacitance		-	2.5	-	nF
C_{res}	Reverse Transfer Capacitance		-	0.72	-	nF
I_{CES}	Collector-Emitter Leakage Current	$V_{CE}=1200V, V_{GE}=0V$	-	-	5.0	mA
I_{GES}	Gate Leakage Current, Forward	$V_{GE}=20V, V_{CE}=0V$	-	-	400	nA
	Gate Leakage Current, Reverse	$V_{GE}=-20V, V_{CE}=0V$	-	-	-400	nA

$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=600V$ $V_{GE}=\pm 15V$ $I_C=200A$ $R_G=10\Omega$ Inductive Load $T_C=25^\circ C$	-	60	-	ns
t_r	Turn-on Rise Time		-	92	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	525	-	ns
t_f	Turn-off Fall Time		-	37	-	ns
E _{on}	Turn-on Switching Loss		-	30	-	mJ
E _{off}	Turn-off Switching Loss		-	6.7	-	mJ
E _{ts}	Total Switching Loss	-	36.7	-	mJ	
$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=600V$ $V_{GE}=\pm 15V$ $I_C=200A$ $R_G=10\Omega$ Inductive Load $T_C=125^\circ C$	-	65	-	ns
t_r	Turn-on Rise Time		-	110	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	610	-	ns
t_f	Turn-off Fall Time		-	55	-	ns
E _{on}	Turn-on Switching Loss		-	45	-	mJ
E _{off}	Turn-off Switching Loss		-	10	-	mJ
E _{ts}	Total Switching Loss	-	55	-	mJ	
R _{th j-c}	Thermal resistance, junction to case				0.12	K/W
T _{vj op}	Temperature under switching condition		-40		125	°C

Diode Maximum Rated Values (TC=25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V _{RRM}	Repetitive peak reverse voltage	1200	V
I _F	Continuous DC Forward Current	200	A
I _{FRM}	Repetitive Peak Collector Current (tp= 1 ms)	400	A

Diode Characteristics (TC=25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V _F	Diode Forward Voltage	I _F =200A V _{GE} =0V T _C =25°C		1.8	2.3	V
		I _F =200A V _{GE} =0V T _C =125°C		1.5		V
I _{RM}	Peak reverse recovery current	I _C =200A V _R =600V -di/dt=1000A/us V _{GE} =-15V T _C =25°C		130		A
		I _C =200A V _R =600V -di/dt=1000A/us V _{GE} =-15V T _C =125°C		165		A

Q _{r r}	Diode Reverse Recovery Charge	I _C =200A V _R =600V -di/dt=1000A/us V _{GE} =-15V T _C =25°C	-	21.6		uC
		I _C =200A V _R =600V -di/dt=1000A/us V _{GE} =-15V T _C =125°C		38		uC
E _{rec}	Reverse recovery energy	I _C =200A V _R =600V -di/dt=1000A/us V _{GE} =-15V T _C =25°C		7.3		mJ
		I _C =200A V _R =600V -di/dt=1000A/us V _{GE} =-15V T _C =125°C		13		mJ
R _{th j-c}	Thermal resistance, junction to case				0.19	K/W
T _{vj op}	Temperature under switching condition		-40		125	°C

Module

Isolation test voltage	RMS, f = 50 Hz, t = 1 min	V _{ISOL}	2.5	kV
Material of module baseplate			Cu	
Internal isolation	basic insulation (class 1, IEC 61140)		Al ₂ O ₃	
Creepage distance	Terminal to terminal		20	mm
Clearance	Terminal to terminal		11	mm
Comperative tracking index		CTI	>425	

			min.	typ.	Max.
Thermal resistance, case to heatsink		R _{th c-H}		0.01	K/W
Stray inductance module		L _{sCE}		20	nH
Module lead resistance, terminals - chip		R _{cc+ee}		0.7	mΩ
Storage temperature		T _{stg}	-40	125	°C
Mounting torque for modul mounting		M	3	6	Nm
Terminal connection torque		M	2.5	5	Nm
Weight		G		340	g

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature

Typical Performance Characterist




Figure 1. transient thermal impedance IGBT Figure




Figure 2. transient thermal impedance Diode

Disclaimers

JIAEN Semiconductor Co., Ltd reserves the right to make changes without notice in order to improve reliability, function or design and to discontinue any product or service without notice. Customers should obtain the latest relevant information before orders and should verify that such information is current and complete. All products are sold subject to JIAEN's terms and conditions supplied at the time of order acknowledgement.

JIAEN Semiconductor Co., Ltd warrants performance of its hardware products to the specifications at the time of sale, Testing, reliability and quality control are used to the extent JIAEN deems necessary to support this warrantee. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

JIAEN Semiconductor Co., Ltd does not assume any liability arising from the use of any product or circuit designs described herein. Customers are responsible for their products and applications using JIAEN's components. To minimize risk, customers must provide adequate design and operating safeguards.

JIAEN Semiconductor Co., Ltd does not warrant or convey any license either expressed or implied under its parent rights, nor the rights of others. Reproduction of information in JIAEN's datasheets or data books is permissible only if reproduction is without modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice. JIAEN Semiconductor Co., Ltd is not responsible or liable for such altered documentation.

Resale of JIAEN's products with statements different from or beyond the parameters stated by JIAEN Semiconductor Co., Ltd for that product or service voids all express or implied warranties for the associated JIAEN's product or service and is unfair and deceptive business practice. JIAEN Semiconductor Co., Ltd is not responsible or liable for any such statements.